

LumeLit 2ft 4ft I BEAM HI Bay SERIES

Project Name: _____

Engineered for balanced LED lumen output with long-rated life. Smart Ready for daylight, and bi-level dimming, motion and occupancy sensor functions.

Features

Sizes	2 ft and 4 ft
Finish	Pure White Semi-Gloss
Diffuser	Anti-UV Frosted Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

Construction

Manufactured for durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

Applications

Primary use as high-bay luminaires for commercial and industrial buildings. Pendant or surface mounted specifically for indoor high ceiling spaces above 25 feet.

Listings

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. View DLC Premium listing at: designlights.org/qpl



Model NO.	Wattage	Voltage	CCT	Light Output	Life	Item#	Price
LumeLIT/HIBAY2/90/4k/	90	120/277	4000	11700LM	75000	L0065	75.00
LumeLIT/HIBAY2/90/5k/	90	120/277	5000	11700LM	75000	L0066	75.00
LumeLIT/HIBAY2/110/4k/	110	120/277	4000	14300LM	75000	L0067	85.50
LumeLIT/HIBAY2/110/4k/	110	120/277	4000	14300LM	75000	L0068	85.50
LumeLIT/HIBAY2/162/4k/	162	120/277	4000	21060LM	75000	L0069	103.50
LumeLIT/HIBAY2/162/5k/	162	120/277	5000	21060LM	75000	L0070	103.50
LumeLIT/HIBAY4/225/4k/	225	120/277	4000	29250LM	75000	L0071	151.00
LumeLIT/HIBAY4/225/5k/	225	120/277	5000	29250LM	75000	L0072	151.00
LumeLIT/HIBAY4/321/4k/	321	120/277	4000	41730LM	75000	L0073	187.00
LumeLIT/HIBAY4/321/5k/	321	120/277	5000	41730LM	75000	L0074	187.00
Occupancy Sensor						P0015	36.50
Pendant Mount Bracket						P0016	8.50
Wire Guard 90-321W						P0017	16.50

MODEL INCLUDES: V HOOKS AND CHAINS AS WELL AS POLYCARBONATE LENS.



Lighting & Electrical Supply

