

LumeLIT Tunable Wattage/Color Vapor Tight Project:

FEATURES	
Lumen Output	4420 to 11700 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3500K, 4000K, 5000K)
IP Rating	UL Wet Location
Size	4-FT, 8-FT
Warranty	7 Years



APPLICATIONS

Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for harsh environments, manufacturing, production, processing, R&D, parking garages, stairwells, and wet locations.

CONSTRUCTION

Manufactured for durability with injection molded polycarbonate to resist corrosion, discoloration, and scratching. Stainless steel clips lock the lens cover to resist dust, moisture and vapors. UL Wet Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming, Tunable CCT (3500K, 4000K, 5000K) and Tunable Wattage (4-FT, 34W, 38W, 45W) or (8-FT, 65W, 75W, 90W). Operating temperatures -40°F to 104°F (-40°C to 40°C).

MOUNTING

Surface Mounts standard. Optional V-Hooks and Chain ready.

OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

WARRANTY

7 year exclusive limited warranty. [View complete product warranty information](#)

TUNABLE CORRELATED COLOR TEMPERATURES (CCT)



Model	Wattage	Voltage	Lumens	Size	CCT	Item#	Price
LumeLIT/Tunable Vapor Tight	34W	120/277	4420	4-FT	(3500K	L0053	63.00
	38W		4940		4000K		
	45W		5850		5000K		
LumeLIT/Tunable Vapor Tight	65W	120/277	8450	8-FT	(3500K	L0054	137.00
	75W		9750		4000K		
	90W		11700		5000K		
Chain and V Hooks Kit						P0010	3.15



Lighting & Electrical Supply

