

LumeLIT Wattage/Color Tunable Strip Light

Project:

9X Setting Combinations. Select (3500K, 4000K, 5000K). Select 4-FT (25W, 30W, 40W) or Select 8-FT (54W, 60W, 65W). Smart Sensor Ready for daylight, bi-level dimming, and motion detection.

FEATURES	
Lumen Output	3250 to 6450 lumens
Efficiency	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3500K, 4000K, 5000K)
IP Rating	IP64 Wet Location
Size	4-FT, 8-FT
Warranty	7 Years

APPLICATIONS
Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, work-stations, and covered decks.

CONSTRUCTION
Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. IP64 Wet Location rated for protection against solid objects 1.0mm diameter and greater, splashing water; IEC 60529.

ELECTRICAL
Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable CCT (3500K, 4000K, 5000K) and Tunable Wattage (4-FT, 25W, 30W, 40W) or (8-FT, 54W, 60W, 65W). Operating temperatures -4°F to 104°F (-20°C to 40°C).

MOUNTING
Aluminum Surface /Chain Hang Mounts standard. Optional V-Hooks and Chains for hanging available.

OPTICS
Anti-UV Frosted Prismatic Polycarbonate Lens.

CONTROLS
Fixture mounted daylight, bi-level dimming, and motion detection sensor available.

LISTINGS
DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

WARRANTY
7 year exclusive limited warranty. View complete product warranty information



TUNABLE CORRELATED COLOR TEMPERATURES (CCT)



Model	Wattage	Voltage	Lumens	Size	CCT	Item#	Price
LumeLIT/Tunable Linear Strip	25W	120/277	3250	4-FT	3500K	L0051	46.00
	30W		3900		4000K		
	40W		5200		5000K		
LumeLIT/Tunable Linear Strip	54W	120/277	7020	8-FT	3500K	L0052	88.00
	60W		7900		4000K		
	65W		8450		5000K		

4-FT Wire Guard	\$ 15.00
8-FT Wire Guard	\$ 26.00
4-FT Frosted Prismatic Polycarbonate Replacement Lens	\$ 12.00
8-FT Frosted Prismatic Polycarbonate Replacement Lens	\$ 20.00
10-FT Galvanized Aircraft Cables for Hanging (Pair)	\$ 9.00
INSTALLED - Smart Sensor for Photocell and PIR Bi-Level Motion Dimming	\$ 37.00
Wireless Remote Controller to Smart Sensor	\$ 15.00
INSTALLED - Emergency Battery Backup Tunable, Select (10W, 15W, 20W)	\$ 80.00



Lighting & Electrical Supply

