

LumeLIT TLED HYBRID TYPE A + B

Project Name: _____

with or without a ballast. Supports single-ended or double-ended installations and compatible with shunted or non-shunted tombstones.

FEATURES	
Lumen Output	1860 to 2790 lumens
Efficacy	155 lm/W
Input Voltage	120-277V
Driver	Dual Mode Internal Driver (Type A+B)
Installation	Single or Double Ended
Dimmable	No
Size	4-FT
CCT	4000K or 5000K
IP Rating	IP44 Wet Location
Warranty	5 Years



APPLICATIONS

Premium indoor replacement lamp intended to replace 4 foot T8 or T12 fluorescent lamps with a G13 base for linear lighting fixtures. Suitable for use in linear troffers, wraparounds, and shop lights.

CONSTRUCTION

Manufactured for durability and heat dissipation using aluminum sheet backing. IP44 Wet Location rated for protection against solid objects 1.0mm diameter and greater, splashing water: IEC 60529.

ELECTRICAL

Input voltages 120-277V. Type A+B, Hybrid plug and play to operate with or without a ballast. Single or Double-Ended Power installations. Operating temperatures -4°F to 104°F (-20°C to 40°C).

OPTICS

Anti-UV Frosted Polycarbonate Lens standard. Optional Clear Polycarbonate Lens available.

CONTROLS

Compatible with ON/OFF occupancy sensors.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

WARRANTY

5 year exclusive limited warranty. View complete product warranty information

CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: 12W, 15W, 18W

Power Factor: >0.9

Total Harmonic Distortion (THD): <15%

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: 1860 (12W), 2325 (15W), 2790 (18W)

Lumens Per Watt: 155 lm/W

Color Correlated Temperature (CCT): 4000K, 5000K

Dimmable: No

Color Rendering Index (CRI): >80

L70: 50000 hours

ORDERING INFORMATION

MODEL	SIZE	Wattage	Voltage	Lumens	CCT	Dimming	Color	Item#	Price.
LumeLIT/-T8-4F-12	4FT	12	120/277	1860	4K	NO	4000	L0055	5.65
LumeLIT/-T8-4F-12	4FT	12	120/277	1860	5K	NO	5000	L0056	5.65
LumeLIT/-T8-4F-15	4FT	15	120/277	2325	4K	NO	4000	L0057	5.65
LumeLIT/-T8-4F-15	4FT	15	120/277	2325	5K	NO	5000	L0058	5.65
LumeLIT-T8-4F-18	4FT	18	120/277	2790	4K	NO	4000	L0059	5.65
LumeLIT-T8-4F-18	4FT	18	120/277	2790	5K	NO	5000	L0060	5.65



Lighting & Electrical Supply

