

# LumeLIT TLED HYBRID TYPE A + B

**Project Name:**

installations for use without a ballast. Compatible with shunted or non-shunted tombstones.

### FEATURES

Lumen Output	5200 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Driver	Internal Driver, Line Voltage (Type B)
Installation	Double Ended
Dimmable	No
Size	8-FT
CCT	4000K or 5000K
IP Rating	IP44 Wet Location
Warranty	5 Years

### APPLICATIONS

Premium indoor replacement lamp intended to replace 8 foot T8 or T12 fluorescent lamps with FA8 Single-Pin, or R17D Rotatable base, for linear lighting fixtures. Suitable for use in linear wraparounds and shop lights.

### CONSTRUCTION

Manufactured for durability and heat dissipation using aluminum sheet backing. IP44 Wet Location rated for protection against solid objects 1.0mm diameter and greater, splashing water: IEC 60529.

### ELECTRICAL

Input voltages 120-277V, Type B, to operate without a ballast. Double-Ended Power installations for FA8 or R17D Rotatable end caps. Operating temperatures -4°F to 104°F (-20°C to 40°C).

### OPTICS

Anti-UV Frosted Polycarbonate Lens standard. Optional Clear Polycarbonate Lens available.

### CONTROLS

Compatible with ON/OFF occupancy sensors.

### LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

### WARRANTY

5 year exclusive limited warranty. View complete product warranty information



### CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



MODEL	SIZE	Wattage	Voltage	Lumens	CCT	Dimming	Item#	Price.
LumeLIT/-T8-8F-40/FAB	8FT	40	120/277	5200	4K	NO	L0061	16.25
LumeLIT/-T8-8F-40/FAB	8FT	40	120/277	5200	5K	NO	L0062	16.25
LumeLIT/-T8-8F-40/R17D	8FT	40	120/277	5200	4K	NO	L0063	16.25
LumeLIT/-T8-8F-40/R17D	8FT	40	120/277	5200	5K	NO	L0064	16.25



**Lighting & Electrical Supply**