

LumeLIT Tun able Color/ Wattage Wall pack **Project:**

Wattages, Select (40W, 50W, 60W, 80W) or Select (90W, 100W, 110W, 120W).

FEATURES	
Lumen Output	5000 to 15000 lumens
Efficacy	125 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	5000K
IP Rating	IP65 Wet Location
Warranty	7 Years



APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. IP65 Wet Location rated for dust-tight, water jets: IEC 60529.

ELECTRICAL

Input voltages 120-277V with 0-10V Continuous Dimming. Operating temperatures -22°F to 113°F (-30°C to 45°C). Surge Protection Rating L-N: 2kV, L/N-PE: 4kV: IEC 61000-4-5.

OPTICS

Anti-UV Clear Prismatic Tempered Lens.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

WARRANTY

7 year exclusive limited warranty. View complete product warranty information



CORRELATED COLOR TEMPERATURE (CCT)

5000K



PHYSICAL DIMENSIONS

14.25"L x 7.56"W x 9.36"H
W



Model	Wattage	Voltage	Lumen	CCT	Item#	Price
LumeLIT/TunableWallPack80W	40W	120/277	5000	5000	L0020	86.50
	50W		6250			
	60W		7500			
	80W		10000			
LumeLIT/TunableWallPack120W	90W	120/277	11250	5000	L0021	117.00
	100W		12500			
	110W		13750			
	120W		15000			



Lighting & Electrical Supply

