

# LumeLit UFO HI Bay Series

**Project Name:**

program Smart Sensor functions in minutes to automate or control sensitivity and brightness levels for photocell, bi-level dimming, and motion detection.

**Features**

IP Rating	IP65 - Wet Location
Finish	Black Satin
Diffuser	NSF Certified Clear Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

**Construction**

Manufactured for wet-location durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

**Applications**

Primary use as high-bay luminaires for commercial and industrial buildings. Pendant or hook mounted specifically for indoor high ceiling spaces above 25 feet.

**Listings**

DLC listed, ETL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. IP65 rated for wet location use. NSF Certified lens. View DLC listing at: [designlights.org/qpl](http://designlights.org/qpl)

**Warranty**

7 year exclusive limited warranty. View complete product warranty



**Performance**

Wattage	See ordering information.
Voltage	120-277V or 277-480V
Frequency	50/60 Hz
Efficacy	150 lm/W
CCT	4000K or 5000K
CRI	≥ 80
Power Factor	≥ 0.9
THD	≤ 15%
Operating Temp.	-20°C to 45°C (-4°F to 113°F)
Dimming	0-10V

Model NO.	Wattage	Voltage	CCT	Light Output	Life	Item#	Price
LumeLIT/UFO/HIbay/100W/4K	100	120/277	4000	14000LM	75000	L0075	84.00
LumeLIT/UFO/HIbay/100W/5K	100	120/277	5000	14000LM	75000	L0076	84.00
LumeLIT/UFO/HIbay/150W/4K	150	120/277	4000	21000LM	75000	L0077	105.00
LumeLIT/UFO/HIbay/150W/5K	150	120/277	5000	21000LM	75000	L0078	105.00
LumeLIT/UFO/HIbay/200W/4K	200	120/277	4000	28000LM	75000	L0079	133.00
LumeLIT/UFO/HIbay/200W/5K	200	120/277	5000	28000LM	75000	L0080	133.00
LumeLIT/UFO/HIbay/240W/4K	240	120/277	4000	33600LM	75000	L0081	146.00
LumeLIT/UFO/HIbay/240W/5K	240	120/277	5000	33600LM	75000	L0082	146.00
LumeLIT/UFO/HIbay/150W/4K	150	277/480	4or5K	21120LM	75000	L0083	148.00
LumeLIT/UFO/HIbay/240W/5K	240	277/480	4or5K	33600LM	75000	L0084	184.00
Frosted Polycarbonate Lens						P0001	12.00
60-90- or 120-Degree Reflector						P0002	32.00
Yoke Mount						P0003	12.00
Occupancy Sensor						P0004	32.00
Sensor Remote						P0005	26.00

**Model Includes Surface Mount, Black Satin Housing, Clear Polycarbonate Lens, IP65 Wet Location, Surge Protection**



**Lighting & Electrical Supply**

